

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE
REMONUMENTATION OF CERTAIN IDENTIFIED CORNERS
ON THE WEST BOUNDARY OF
TOWNSHIP 50 NORTH, RANGE 84 WEST,
OF THE SIXTH PRINCIPAL MERIDIAN,
IN THE STATE OF WYOMING.

EXECUTED BY

JOEL T. EBNER

CADASTRAL SURVEYOR

Under Special Instructions dated JUNE 11 1990, approved JUNE 11, 1990, which provided for the surveys included under Group Number 540, and assignment instructions dated JULY 28, 1999.

Survey commenced JULY 20, 1999

Survey completed AUGUST 4, 1999

INDEX DIAGRAM

269

Township 50 North, Range 84 West

REMONUMENTATION OF CERTAIN CORNERS

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
2					
30	29	28	27	26	25
2					
31	32	33	34	35	36
1					

T. 50 N., R. 84 W., Sixth Principal Meridian, Wyoming

CHAINS

The following field notes are those of the remonumentation of certain identified corners on the west boundary of Township 50 North, Range 84 West, of the Sixth Principal Meridian, in the State of Wyoming.

Remonumentation of Corners on the West Boundary of
T. 50 N., R. 84 W., Sixth Principal Meridian, Wyoming

(Remonumentation of certain corners of the survey
executed by William O. Downey and Mortimer N. Grant in 1881)

The cor of Tps. 49 and 50 N., Rs. 84 and 85 W., monumented with a granite stone 27x21x6 ins., loosely set 8 ins. in the ground, in a collar of stone, plainly mkd. 6 notches on N. and S. edges and 6 grooves on E. and W. faces.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T50N	
R85W	R84W
S 36	S 31
<hr/>	
S 1	S 6
T49N	
1999	

from which

A pine, 8 ins. diam., bears S. 65½° E, 24 lks. dist., mkd. T49N R84W S6 BT.

A pine, 12 ins. diam., bears S. 78° W, 21 lks. dist., mkd. T49N R85W S1 BT.

Bury the original cor. stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.

Cor. is located 40 lks. S. of South Fork Clear Creek, course ENE.

T. 50 N., R. 84 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>The cor. of secs. 25, 30, 31 and 36, monumented with a granite stone, 12x9x7 ins., firmly set 4 ins. in the ground, in a collar of stone, plainly mkd. 5 grooves on N. face, no other mks. visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, supported by a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td colspan="2">T50N</td></tr> <tr><td>R85W</td><td>R84W</td></tr> <tr><td>S 25</td><td>S 30</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 36</td><td>S 31</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Bury the original cor. stone alongside the iron post.</p> <hr/> <p>The cor. of secs. 19, 24, 25 and 30, monumented with a granite stone, 17x15x7 ins., firmly set 6 ins. in the ground, in a collar of stone, plainly mkd. 4 grooves on N. face and 2 notches on S. edge.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td colspan="2">T50N</td></tr> <tr><td>R85W</td><td>R84W</td></tr> <tr><td>S 24</td><td>S 19</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 25</td><td>S 30</td></tr> <tr><td colspan="2">1999</td></tr> </table> </div> <p>Bury the original cor. stone alongside the iron post and raise a mound of stone, 5 ft. base, 4 ft. high W. of the cor.</p> <hr/>	T50N		R85W	R84W	S 25	S 30	<hr/>		S 36	S 31	1999		T50N		R85W	R84W	S 24	S 19	<hr/>		S 25	S 30	1999	
T50N																									
R85W	R84W																								
S 25	S 30																								
<hr/>																									
S 36	S 31																								
1999																									
T50N																									
R85W	R84W																								
S 24	S 19																								
<hr/>																									
S 25	S 30																								
1999																									

FIELD ASSISTANTS

[illegible]


CERTIFICATE OF SURVEY

272

I, Joel T. Ebner, Cadastral Surveyor, HEREBY CERTIFY upon honor that in pursuance of special instructions bearing date of the 11th day of June, 1990, I have remonumented certain identified corners on the west boundary of Township 50 North, Range 84 West, of the Sixth Principal Meridian, in the State of Wyoming, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JUL 30 2001

(Date)



(Cadastral Surveyor)


CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Cheyenne, Wyoming

The foregoing field notes of the remonumentation of certain identified corners on the west boundary of Township 50 North, Range 84 West, of the Sixth Principal Meridian, in the State of Wyoming, executed by Joel T. Ebner, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUL 30 2001

(Date)



(Signature of Authorized Officer)